




Model: 9HD7M

## 9 inch monitor metal

This 9 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 9 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting. The 9HD7M can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1200 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 218 x 150 x 36 mm



## General

Manufacturer	Beetronics
Item number	9HD7M
Previous model	9HDM
Product name	9 inch monitor metal
Warranty	2 years
User manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Panel

Diagonal size	9.0 inches (228 mm)
Panel type	IPS-LCD
Aspect ratio	16:10 (16:9, 4:3 adjustable)
Response time	10 ms
MTBF	50K
Native resolution	1920 x 1200
Supported resolutions	1920 x 1200 (max), 640 x 480 (min)
Pixels per inch	254 PPI
Backlight	LED
Brightness	450 cd/m <sup>2</sup>
Contrast	900:1
Viewing angle	178° horizontal, 178° vertical

## Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
AUX input	1x
AUX output	1x
USB-A	1x integrated USB media player

## Size & weight

Colour	Black
Dimensions (without stand)	218 x 150 x 36 mm
Image size	193 x 121 mm
Weight	900 grams (1300 gram with stand)

## Features and functions

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, portrait, face-up
USB media player	The monitor is equipped with a built-in USB media player.

## Power

Input voltage	DC 9-33V
Consumption	typical: 7.7 W (on), 0.4 W (standby)
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-2A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

## Environmental

Max. non-stop operating time	24/7
Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +70°C
Operating humidity	20% - 90% non-condensing

## Mounting

Wall mount	<input checked="" type="checkbox"/> VESA (75 mm)
Flush mount	<input checked="" type="checkbox"/> Mounting strips included
Stand	<input checked="" type="checkbox"/> Adjustable and detachable

## Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, EN60601, CCC
----------------	---

## Package content

Includes	Monitor, Stand, Remote control, Mounting strips, AC power adapter, Manual
----------	---

## Compatible accessories

Dimmer	Compatible with external dimmer (DMK7/DMK8)
Rack mounting	Compatible with 19 inch rack mount kit (RMK2)
Wall mounting	Compatible with flat wall mount bracket (VWB1)
Stand	VDK3 included as standard



