




Model: 17VG7M

17 Inch Monitor Metal (5:4)

This 17 inch monitor has a matte IPS panel with a 5:4 aspect ratio. The monitor delivers a crisp image quality with excellent 178° viewing angles. The 17 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting.

- ✓ 5:4 aspect ratio
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 372 x 305 x 40 mm



General

Manufacturer	Beetronics
Product line	Monitor Series
Product name	17 Inch Monitor Metal (5:4)
Item number	17VG7M
Previous model	17VGM
Product type	Monitor
Warranty	2 years
User manual	Download PDF
Quickstart	Download PDF

Display architecture

Diagonal size	17.0 inches (432 mm)
Aspect ratio	5:4
Native resolution	1280 x 1024
Pixels per inch	96 PPI
Panel type	IPS-LCD
Backlight	LED
Surface	Anti-glare hard coating (3H)
Supported orientation	Landscape, portrait, face-up

Display performance

Maximum brightness	250 nits (typical)
Minimum brightness	1 nit
Contrast	1000:1
Viewing angle	178° horizontal, 178° vertical
Response time	10 ms
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Color encoding system	PAL/NTSC/SECAM

Operational features

Audio	Dual integrated speakers
USB media player	Built-in USB media player with auto-play on power-up and continuous loop playback. Supports common video formats such as: MP4, AVI, MKV, MOV, MPG.
Key-lock	The control buttons can be blocked.
Auto-on	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable backlight brightness via remote control or optional dimmer.
Mirroring	Teleprompter compatible. Image can be horizontally and vertically mirrored.

Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
USB-A	1x integrated USB media player
AUX input (3.5mm)	1x
AUX output (3.5 mm)	1x

Mechanical

Dimensions (without stand)	372 x 305 x 40 mm
Image size	337 x 270 mm
Weight	3000 grams (3700 grams with stand)
Colour	Black

Mounting

Wall mount	✔ VESA 100x100mm
Flush mount	✔ Mounting strips included
Stand	✔ Adjustable and detachable
Supported mounting orientations	Landscape, portrait, face-up

Power

Input voltage	DC 10-36V
Consumption	20 W (on), 0.4 W (standby)
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 19V-2.5A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

Environmental

Max. non-stop operating time	24/7
Operating temperature	-10°C to +60°C (14°F to 140°F)
Storage temperature	-20°C to +70°C (-4°F to 158°F)
Operating humidity	10% - 90% non-condensing
MTBF	50K

Compliance & regulations

Regional standards	CE, UKCA, FCC (Part 15), ISED (ICES-003), CCC
Environmental standards	RoHS, REACH, WEEE, California Proposition 65, Conflict minerals (3TG; supplier declaration-based)
Industry standards	Maritime: IEC 60945, DNV-CG-0339 (requires BEE-PSU1-MAR); Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455; Medical: EN 60601-1, EN 60601-1-2 (requires BEE-PSU1-MED)
Compliance scope	Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration.
Compliance statement	Download PDF

Package content

Includes	Monitor, mounting strips, stand, remote control, power adapter, quickstart
----------	----------------------------------------------------------------------------

Compatible accessories

Infrared extension	Compatible with infrared extender (IRC7)
Dimmer	Compatible with external dimmer (DMK7/DMK8)
Rack mounting	Compatible with 19 inch rack mount kit (RMK2)
Wall mounting	Compatible with flat wall mount bracket (VWB1)
Stand	Compatible with VDK6 metal stand



