




Model: 15TS7

## 15 Inch Touchscreen

This Full HD 15 inch touchscreen has a reliable multi-touch panel which ensures accurate operation. The 15TS7 provides crystal-clear image quality with excellent 178° viewing angles and is compatible with Windows, Mac & Linux operating systems. The touchscreen monitor is designed for professional applications and suitable for intensive use.

- ✓ Full HD multi-touch panel
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Wall, desktop
- ✓ External dimensions: 373 x 232 x 33 mm



## General

Manufacturer	Beetronics
Item number	15TS7
Product name	15 Inch Touchscreen
Warranty	2 years
User manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Supported operating systems

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, 8.1 Industry, IoT Enterprise
macOS	Sequoia, Sonoma, Ventura
Linux	All Linux distributions
ChromeOS	All ChromeOS versions
Brightsign	All BrightsignOS versions
Samsung DeX	All Samsung DeX versions

## Panel

Diagonal size	15.6 inches (395 mm)
Panel type	IPS-LCD
Aspect ratio	16:9 (4:3 adjustable)
Response time	10 ms
MTBF	50K
Native resolution	1920 x 1080
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels per inch	146 PPI
Backlight	LED
Brightness	350 cd/m <sup>2</sup>
Contrast	700:1
Color encoding system	PAL/NTSC/SECAM
Viewing angle	178° horizontal, 178° vertical
Surface	Tempered glass
Touch technology	Capacitive, 10-point multi-touch (PCAP)
Touch control	Stylus, hand, glove

## Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
USB-A	Only for touchscreen functionality
AUX input (3.5mm)	1x
AUX output (3.5 mm)	1x

## Size & weight

Colour	Black
Dimensions (without stand)	373 x 232 x 33 mm
Active area	344 x 194 mm
Weight	1200 grams (1800 grams with stand)

## Features and functions

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, portrait, face-up

## Power

Input voltage	DC 9-33V
Consumption	typical: 11.2 W (on), 0.4 W (standby)
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-3A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

## Environmental

Max. non-stop operating time	24/7
Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +70°C
Operating humidity	20% - 85% non-condensing

## Mounting

Wall mount	✔ VESA 75x75mm
Flush mount	✔ Possible, no accessories available
Stand	✔ Adjustable and detachable

## Certifications & Standards

IP rating	IP65 front panel
Impact protection	IK08
Certifications	CE, FCC, RoHS, REACH, WEEE, UKCA, e-Mark, EN50155, EN60601-1, EN60601-1-2, CCC, CAN ICES-003(A)/NMB-003(A)

## Package content

Includes	Touchscreen, AC power adapter, Remote control, USB cable, Stand, Manual
----------	---

## Compatible accessories

Infrared extension	<a href="#">Compatible with infrared extender (IRC7)</a>
Rack mounting	<a href="#">Compatible with 19 inch rack mount kit (RMK2)</a>
Wall mounting	<a href="#">Compatible with flat wall mount bracket (VWB1)</a>
Stand	VDK4 included as standard
Touch pen	<a href="#">Compatible with CTS7 capacitive touchscreen stylus</a>



