




Model: 12HD7

## 12 Inch Monitor

This 12 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 12 inch monitor has a lightweight housing and is ideal for desktop and wall mounting. The 12HD7 can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1080 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Wall, desktop
- ✓ External dimensions: 284 x 179 x 32 mm



## General

Manufacturer	Beetronics
Product line	Monitor Series
Product name	12 Inch Monitor
Item number	12HD7
Previous model	12HD5
Product type	Monitor
Warranty	2 years
User manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Display architecture

Diagonal size	11.6 inches (296 mm)
Aspect ratio	16:9 (4:3 adjustable)
Native resolution	1920 x 1080
Pixels per inch	190 PPI
Panel type	IPS-LCD
Backlight	LED
Surface	Anti-glare hard coating (3H)
Supported orientation	Landscape, portrait, face-up

## Display performance

Maximum brightness	300 nits (typical)
Minimum brightness	1 nit
Contrast	1000:1
Viewing angle	178° horizontal, 178° vertical
Response time	10 ms
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Color encoding system	PAL/NTSC/SECAM

## Operational features

Audio	Dual integrated speakers
USB media player	Built-in USB media player with auto-play on power-up and continuous loop playback. Supports common video formats such as: MP4, AVI, MKV, MOV, MPG.
Key-lock	The control buttons can be blocked.
Auto-on	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable backlight brightness via remote control or optional dimmer.
Mirroring	Teleprompter compatible. Image can be horizontally and vertically mirrored.

## Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
USB-A	1x integrated USB media player
AUX input (3.5mm)	1x
AUX output (3.5 mm)	1x

## Mechanical

Dimensions (without stand)	284 x 179 x 32 mm
Image size	258 x 142 mm
Weight	600 grams (1000 grams with stand)
Colour	Black

## Mounting

Wall mount	✔ VESA 75x75mm
Flush mount	✔ Possible, no accessories available
Stand	✔ Adjustable and detachable
Supported mounting orientations	Landscape, portrait, face-up

## Power

Input voltage	19V DC
Operating voltage range	9-36V DC
Power consumption	11 W (on), 0.4 W (standby)
Power supply	External DC power supply included
Included power adapter	Input: 100-240V AC, 50/60Hz, Output: 19V DC, 1.5A
Power connector	5.5 mm x 2.1 mm DC barrel connector
DC cable length	1.5 m
AC power cord length	1.0 m

## Environmental

Max. non-stop operating time	24/7
Operating temperature	-10°C to +60°C (14°F to 140°F)
Storage temperature	-20°C to +70°C (-4°F to 158°F)
Operating humidity	10% - 90% non-condensing
MTBF	50K

## Compliance & regulations

Regional standards	CE, UKCA, FCC (Part 15), ISED (ICES-003), CCC
Environmental standards	RoHS, REACH, WEEE, California Proposition 65, Conflict minerals (3TG; supplier declaration-based)
Industry standards	Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455
Compliance scope	Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration.
Compliance statement	<a href="#">Download PDF</a>

## Package content

Includes	Monitor, stand, remote control, power adapter, quickstart
----------	---

## Compatible accessories

Rack mounting	<a href="#">Compatible with 19 inch rack mount kit (RMK2)</a>
Wall mounting	<a href="#">Compatible with flat wall mount bracket (VWB1)</a>
Stand	VDK3 included as standard



