



Model: 13HD7

13 inch monitor

This 13 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 13 inch monitor has a lightweight housing and is ideal for desktop and wall mounting. The 13HD7 can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1080 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Wall, desktop
- ✓ External dimensions: 318 x 200 x 33 mm



General

| | |
|--------------|------------------------------|
| Manufacturer | Beetronics |
| Item number | 13HD7 |
| Product name | 13 inch monitor |
| Warranty | 2 years |
| User manual | Download PDF |
| Quickstart | Download PDF |

Panel

| | |
|-----------------------|------------------------------------|
| Diagonal size | 13.0 inches (330 mm) |
| Panel type | IPS-LCD |
| Aspect ratio | 16:9 (4:3 adjustable) |
| Response time | 10 ms |
| MTBF | 50K |
| Native resolution | 1920 x 1080 |
| Supported resolutions | 1920 x 1080 (max), 640 x 480 (min) |
| Pixels per inch | 166 PPI |
| Backlight | LED |
| Brightness | 300 cd/m ² |
| Contrast | 1400:1 |
| Color encoding system | PAL/NTSC/SECAM |
| Viewing angle | 178° horizontal, 178° vertical |

Connectivity

| | |
|------------|--------------------------------|
| HDMI | 1x |
| VGA | 1x |
| BNC (CVBS) | 1x |
| RCA video | 1x |
| AUX output | 1x |
| USB-A | 1x integrated USB media player |

Size & weight

| | |
|--------------------|-----------------------------------|
| Colour | Black |
| Weight | 600 grams (1000 grams with stand) |
| Width | 318 mm |
| Height | 200 mm |
| Thickness | 33 mm |
| Display dimensions | 293 x 165 mm |

Features and functions

| | |
|------------------|--|
| Audio | Integrated speakers |
| Key-lock | The control buttons can be blocked |
| Auto-on | Automatically powers on when it receives current or a signal |
| Dimmable | Adjustable backlight brightness |
| Mirroring | Image can be mirrored, horizontally and vertically |
| Orientation | Landscape, portrait, face-up |
| USB media player | The monitor is equipped with a built-in USB media player. |

Power

| | |
|--------------------------------|--|
| Input voltage | DC 9-33V |
| Consumption | Power consumption (typical): 9.1 W (on), 0.4 W (standby) |
| Power supply | External DC (power adapter included) |
| Power adapter | Input: AC100-240V, 50/60Hz , Output: 12V-2A |
| Power adapter output connector | DC barrel plug 2.1mm x 5.5mm |

Environmental

| | |
|------------------------------|--------------------------|
| Max. non-stop operating time | 24/7 |
| Operating temperature | -20°C to +60°C |
| Storage temperature | -20°C to +70°C |
| Operating humidity | 20% - 80% non-condensing |

Mounting

| | |
|-------------|--|
| Wall mount | <input checked="" type="checkbox"/> VESA (75 mm) |
| Flush mount | <input checked="" type="checkbox"/> Possible, no accessories available |
| Stand | <input checked="" type="checkbox"/> Adjustable and detachable |

Certifications & Standards

| | |
|----------------|---|
| Certifications | CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, EN60601, CCC |
|----------------|---|

Package content

| | |
|----------|--|
| Includes | Monitor, Manual, Remote control, AC power adapter, Stand |
|----------|--|

Compatible accessories

| | |
|---------------|--|
| Rack mounting | Compatible with 19 inch rack mount kit (RMK2) |
| Wall mounting | Compatible with flat wall mount bracket (VWB1) |
| Stand | VDK4 included as standard |



